

Guarantee:

UZIN and DÖLLKEN provides a guarantee of 5 years on all the characteristics guaranteed in the fitting instructions.

- When laying the floor covering, take the generally accepted rules of the trade and technology and the relevant national standard EN into account.

Claims under the guarantee will be excluded if:

- Unusual influences affect the product, in particular of a chemical or mechanical nature
- A utilisation or application has taken place that deviates from the installation instructions.

In all cases, some adhesion tests must be carried out on-site before carrying out the application.

PRODUCT DATA SHEET & APPLICATION INSTRUCTIONS

Special tape for flooring strips in DÖLLKEN core skirting board

Contact 40

Secure gluing of flooring strips in DÖLLKEN core skirting

Product Properties / Benefits:

- ▶ DÖLLKEN – UZIN system guarantee
- ▶ Does not become brittle; permanent and reliable adhesion
- ▶ For PVC/cushioned vinyl, linoleum and colour-strips in C60
- ▶ For needlepunch, secondary, textile and fleece backings, and woven carpet in TS 60/100



Applications:

▶ Suitable carpet and floor covering strips for DÖLLKEN carpet skirting TS 60:

- with jute backings
- with synthetic double backs (SDR), including coarse
- with textile action backs (TR)
- with latex foam backs
- from needle punch
- from Kugelgarn®
- woven textile floor coverings

Recommendation: Use TS 100 Contact 85 for gluing the above mentioned carpet strips into in DÖLLKEN carpet skirting

▶ Suitable carpet and floor covering strips for DÖLLKEN Color skirting boards C 60:

- from PVC/CV
- from linoleum
- from rubber
- DÖLLKEN Colorstrips
- MEDES Alu-Floor

▶ Not guaranteed:

- carpet skirting with PU backs
- wooden strips
- dirt trap runners
- PVC soft skirting boards

for < floor covering strips

IN > DÖLLKEN core skirting boards

also for whipped carpet skirting on sub-surfaces with up to 1.5 mm structure

| | Tape width | Skirting height |
|------------|------------|-----------------|
| Contact 40 | 40 mm | 45 mm – 55 mm |
| Contact 55 | 55 mm | 60 mm – 70 mm |
| Contact 70 | 70 mm | 75 mm – 85 mm |
| Contact 85 | 85 mm | 90 mm – 110 mm |

Technical Data:

Special acrylic adhesive

Will not dry out or become brittle

Application temperature from + 15 °C

Temperature resistant from – 40 °C to + 140 °C (when installed)

Shelf-life min. 2 years in original packaging; store protected from direct sunlight

Do not place rolls on to the cut surfaces without adhesive-resistant paper washers inbetween

APPLICATION INSTRUCTIONS

Preparation:

- ▶ Preparation of the sub-surface: The sub-surface must be dry, hard, flat, able to be walked on and free of grease, dust and silicone, in accordance with the applicable national standard EN.
- ▶ Wallpaper: must be firmly glued into place.
- ▶ Binding the dust: any dust must be consolidated with a solvent-free primer.

What you need:

- ▶ Contact 40, rubber hammer, carpet knife



Application Instructions for TS 60/100

1

- ▶ Apply the Contact 40 to the back of the carpet skirting
- ▶ Do not remove the protective paper yet



2

- ▶ Pull off the two protective papers continuously
- ▶ Fit the carpet skirting into the DÖLLKEN TS 60 core skirting board free from tension and strain



3

- ▶ Tap in everywhere using the rubber hammer → doubles the adhesive force



4

- ▶ Even faster with the Contact applicator



Application tips:

- ▶ Outer corners: Notch elastic coating strips on the back (remove tension), warm and then glue into place without twisting. Bend textile coating strips in advance.
- ▶ Inner corners: Cut through the coating strips and join with instant glue.
- ▶ Fitting together:
 - Bond PVC/CV strips together
 - Join rubber strips and colour strips with instant glue
- ▶ Floor covering strips: Always cut the individual cover strips to shape in the longitudinal or running direction.

Application instructions for C 60

1

- ▶ Fit the Contact 40 directly into the DÖLLKEN C 60 Color skirting board by hand



2

- ▶ Pull the protective paper from the Contact 40
- ▶ Fit the floor covering strips into the DÖLLKEN C 60 Color skirting board



3

- ▶ Rub in or tap in all over with the rubber hammer

